



## Users List – Power Generation-Coal Gasification Waste Incineration/Co-Generation

<b>ATCO ELECTRIC</b> <b>Edmonton, Alberta</b>	1 – 16” Butterfly Control Damper Flanged Ends Carbon Steel Body with Stainless Internals Tadpole Seat
<b>BRONX LEBANESE HOSPITAL</b> <b>Waste Incineration Furnace</b> New York, NY. USA	2 – 59” ID Slide Gate Valve, Refractory Lined Body; Solid Refractory Gate, Isolation for 2350°F Flue Gases @ 10PSIG
<b>CENTRAL SANITATION</b> <b>Waste Incineration Cogen.</b> Pompano Beach, Fl.. USA	5 - 42” Butterfly Valve Pneumatically Operated 3 - 30” Butterfly Valve Pneumatically Operated A387 GR11 Construction 1100°F flue gases @ 26” WC
<b>FERCO</b> <b>Gasification Project</b> Burlington, VT. USA	4-10” 300 ANSI Slide Gate Valve, 316 Stainless Body & Flanges, Hard-Chromed Gate With Stellite® Seat, Pneumatically Actuated 1-6” 300 ANSI Hopper Bottom Slide Gate With 310 Stainless Gate and 316L Body 3 – 8” High Performance BF Valve 150 ANSI A216WCB Body and 316 SST Trim 2 – 10” 1 – 16” BF Control Valve A216WCB With Bettis® SR Actuators & PMV® I/P Positioners, 800°F Gases @ 3 PSIG 1 – 10” BF Control Valve CF8M With Bettis® SR Actuators & PMV® I/P Positioners, 800°F Gases @ 2.5 Psig 2 – 20” 1 – 24” 1 – 6”, 150 ANSI HPBV A216WCB Wafer Body With Rotork® SR Pneumatic Actuator, PMV® Positioner 1 – 16” & 1 – 10” X 10” Slide Gate Valves 150 ANSI All 316L Stainless With D/A Pneumatic Cylinder Operator 1 – 6” & 1 – 4” Knife gate Valves 150 ANSI With Alloy EN30B Gate and Stellite® 6 seats
<b>KEYSPAN ENERGY</b> <b>Ravenswood Co-Gen Project</b> Bayonne, NJ. USA	2-96” Butterfly Valves Flanged Ends Carbon Steel Body and Stainless Trim, With O-Ring Disc edge for Class IV Shutoff
<b>PEEL RESOURCES</b> <b>Waste Incineration Plant</b> Mississauga, Ontario. Canada	12 – 24” X 24” Slide gate valves, Flanged Refractory Lined Body with Ceramic coated 310 SST Gate, For bottom ash service @ 1650°F



## Users List – Power Generation-Coal Gasification Waste Incineration/Co-Generation

<b>ROCKYVIEW HOSPITAL</b> <b>Biological Waste Incinerator</b> Calgary, Alberta. Canada	22" Refractory lined Butterfly Valve flanged ends Alloy 333 Disc & Shafts for Flue gases @ 2200°F
<b>SASKPOWER</b> Saskatoon, Sk. Canada.	2- 60" Double Disc Slide Gate Valve, Flanged Ends, Carbon Steel Body and 316L Stainless Trim With Hydraulic Cylinder operator and Limit Switches For Double Block and Bleed confined space entry service 1 – 48" Same as above
<b>TAMPA ELECTRIC COMPANY</b> <b>Polk County Gasifier</b> Mulberry, Florida. USA	1-14" X 8" Refractory Lined Slide Gate ANSI 1500 2050°F Flue Gases @ 75PSIG, Supertherm Disc Ceramic Seats, Pneumatic operator
<b>TRITON COAL/SHELL OIL</b> <b>Gasification Project</b> Gillette, Wyoming. USA	1 – 48" Flex Wedge Slide Gate Valve, Flanged ends Emergency Vent Valve, With Bettis Linear Cylinder operator Valve Opens in 1 second in case of explosion in hot gas line To vent gases to stack. All 316L Body & Flanges with Hastelloy seat and disc, Double seat for zero leak service. Isolating process gases 1100°F @ 9Psig