



## Users List – Power Generation-Coal Gasification Waste Incineration/Co-Generation

<b>ARKANSAS POWER &amp; LIGHT WHITE BUFF POWER PLANT</b> Redfield, Ar. USA	4-64" x 64" RD300LD Louvered Damper
<b>ATCO ELECTRIC</b> Edmonton, Alberta. Canada	2 – 16" Butterfly Control Damper Flanged Ends Carbon Steel Body with Stainless Internals Tadpole Seat 2 Psig at 900F 2 – 20" Same as above
<b>BRONX LEBANESE HOSPITAL Waste Incineration Furnace</b> New York, NY. USA	2 – 59" ID Slide Gate Valve, Refractory Lined Body; Solid Refractory Gate, Isolation for 2350°F Flue Gases @ 10PSIG
<b>CENTRAL SANITATION Waste Incineration Cogen.</b> Pompano Beach, Fl.. USA	5 - 42" Butterfly Valve Pneumatically Operated 3 - 30" Butterfly Valve Pneumatically Operated A387 GR11 Construction 1100°F flue gases @ 26" WC
<b>FERCO Biomass Gasification Project</b> Burlington, VT. USA	4-10" 300 ANSI Slide Gate Valve, 316 Stainless Body & Flanges, Hard-Chromed Gate With Stellite® Seat, Pneumatically Actuated 1-6" 300 ANSI Hopper Bottom Slide Gate With 310 Stainless Gate and 316L Body 3 – 8" High Performance BF Valve 150 ANSI A216WCB Body and 316 SST Trim 2 – 10" 1 – 16" BF Control Valve A216WCB With Bettis® SR Actuators & PMV® I/P Positioners, 800°F Gases @ 3 PSIG 2 – 20" 1 – 24" 1 – 6", 150 ANSI HPBV A216WCB Wafer Body With Rotork® SR Pneumatic Actuator, PMV® Positioner 1 – 16" & 1 – 10" X 10" Slide Gate Valves 150 ANSI All 316L Stainless With D/A Pneumatic Cylinder Operator 1 – 6" & 1 – 4" Slide Gate Valves 150 ANSI With Alloy EN30B Gate and Stellite® 6 seats
<b>KONIAMBO NICKLE Power Utility New Caledonia</b>	4- 1100mm x 600mm Guillotine – Flanged Ends Zero Leakage Configuration with Cincinnati Blowers to supply Seal air. All 309 Stainless Construction. With AUMA Motor operators. For isolation of 1800F Combustion gases



## Users List – Power Generation-Coal Gasification Waste Incineration/Co-Generation

<b>KEYSPAN ENERGY</b> <b>Ravenswood Co-Gen Project</b> Bayonne, NJ. USA	2-96" Butterfly Valves Flanged Ends Carbon Steel Body and Stainless Trim, With O-Ring Disc edge for Class IV Shutoff
<b>PEEL RESOURCES Waste Incineration Plant</b> Mississauga, Ontario. Canada	12 – 24" X 24" Slide gate valves, Flanged Refractory Lined Body with Ceramic coated 310 SST Gate, For bottom ash service @ 1650°F
<b>OLMSTEAD COUNTY Waste to Energy Facility Unit 3 Expansion</b> Rochester, Mn. USA	2 - 44" Frisch Butterfly Valve, Buttweld Ends Epoxy coated O-ring Seal Disc Edge Seat 304 Stainless Steel Shafts are 17-4 PH H1150 stainless steel, Complete with Limitorque Accutronic MX Electric Actuator With 460V/3Ph/60Hz. NEMA 4X Enclosure Motor, 1 - 28" Same As Above 1 - 24" Same As Above
<b>PIQUA POWER PLANT</b> Piqua , OH	2-58 ½" CB100 BFV 1-67 ½" CB100 BFV 1-55" x 108" FB101 Rectangle Damper 1-39" x 114" FB101 Rectangle Damper
<b>ROCKYVIEW HOSPITAL Biological Waste Incinerator</b> Calgary, Alberta. Canada	22" Refractory lined Butterfly Valve flanged ends Alloy 333 Disc & Shafts for Flue gases @ 2200°F
<b>SASKPOWER</b> Saskatoon, Sk. Canada. Coronach, SK. Canada	2-60" Double Block Slide Gate Valve, Flanged Ends, Carbon Steel Body and 316L Stainless Trim With Hydraulic Cylinder operator and Limit Switches For Double Block and Bleed confined space entry service 2 - 54" Same as above 1 - 48" Same as above 60" Blind Assemblies & Expansion Joints
<b>TAMPA ELECTRIC COMPANY Polk County Gasifier</b> Mulberry, Florida. USA	1-14" X 8" Refractory Lined Slide Gate ANSI 1500 2050°F Flue Gases @ 75PSIG, Supertherm Disc Ceramic Seats, Pneumatic operator
<b>TRITON COAL/SHELL OIL Gasification Project</b> Gillette, Wyoming. USA	1 – 48" Flex Wedge Slide Gate Valve, Flanged ends Emergency Vent Valve, With Bettis Linear Cylinder operator Valve Opens in 1 second in case of explosion in hot gas line To vent gases to stack. All 316L Body & Flanges with Hastelloy seat and disc, Double seat for zero leak service. Isolating process gases 1100°F @ 9Psig



## Users List – Power Generation-Coal Gasification Waste Incineration/Co-Generation

---

<b>State of Wyoming Vet Lab Waste Disposal Incinerator</b> Laramie, WY. USA	56" X 44" Double Disc Slide Gate Valve Flanged Ends With Hydraulic Cylinder operator For isolation of 1880F gases at 20"WC
--	--