



Users List – Power Generation-Coal Gasification Waste Incineration/Co-Generation

ARKANSAS POWER & LIGHT WHITE BUFF POWER PLANT Redfield , AR	4-64" x 64" RD300LD Louvered Damper
ATCO ELECTRIC Edmonton, Alberta	2 – 16" Butterfly Control Damper Flanged Ends Carbon Steel Body with Stainless Internals Tadpole Seat 2 Psig at 900F 2 – 20" Same as above
BRONX LEBANESE HOSPITAL Waste Incineration Furnace New York, NY. USA	2 – 59" ID Slide Gate Valve, Refractory Lined Body; Solid Refractory Gate, Isolation for 2350°F Flue Gases @ 10PSIG
CENTRAL SANITATION Waste Incineration Cogen. Pompano Beach, Fl.. USA	5 - 42" Butterfly Valve Pneumatically Operated 3 - 30" Butterfly Valve Pneumatically Operated A387 GR11 Construction 1100°F flue gases @ 26" WC
FERCO Biomass Gasification Project Burlington, VT. USA	4-10" 300 ANSI Slide Gate Valve, 316 Stainless Body & Flanges, Hard-Chromed Gate With Stellite® Seat, Pneumatically Actuated 1-6" 300 ANSI Hopper Bottom Slide Gate With 310 Stainless Gate and 316L Body 3 – 8" High Performance BF Valve 150 ANSI A216WCB Body and 316 SST Trim 2 – 10" 1 – 16" BF Control Valve A216WCB With Bettis® SR Actuators & PMV® I/P Positioners, 800°F Gases @ 3 PSIG 2 – 20" 1 – 24" 1 – 6", 150 ANSI HPBV A216WCB Wafer Body With Rotork® SR Pneumatic Actuator, PMV® Positioner 1 – 16" & 1 – 10" X 10" Slide Gate Valves 150 ANSI All 316L Stainless With D/A Pneumatic Cylinder Operator 1 – 6" & 1 – 4" Slide Gate Valves 150 ANSI With Alloy EN30B Gate and Stellite® 6 seats
KEYSPAN ENERGY Ravenswood Co-Gen Project Bayonne, NJ. USA	2-96" Butterfly Valves Flanged Ends Carbon Steel Body and Stainless Trim, With O-Ring Disc edge for Class IV Shutoff
PEEL RESOURCES Waste Incineration Plant Mississauga, Ontario. Canada	12 – 24" X 24" Slide gate valves, Flanged Refractory Lined Body with Ceramic coated 310 SST Gate, For bottom ash service @ 1650°F



Users List – Power Generation-Coal Gasification Waste Incineration/Co-Generation

<p>OLMSTEAD COUNTY Waste to Energy Facility Unit 3 Expansion Rochester, Mn. USA</p>	<p>2 - 44" Frisch Butterfly Valve, Buttweld Ends Epoxy coated O-ring Seal Disc Edge Seat 304 Stainless Steel Shafts are 17-4 PH H1150 stainless steel, Complete with Limitorque Accutronic MX Electric Actuator With 460V/3Ph/60Hz. NEMA 4X Enclosure Motor, 1 - 28" Same As Above 1 - 24" Same As Above</p>
<p>PIQUA POWER PLANT Piqua , OH</p>	<p>2-58 ½" CB100 BFV 1-67 ½" CB100 BFV 1-55" x 108" FB101 Rectangle Damper 1-39" x 114" FB101 Rectangle Damper</p>
<p>ROCKYVIEW HOSPITAL Biological Waste Incinerator Calgary, Alberta. Canada</p>	<p>22" Refractory lined Butterfly Valve flanged ends Alloy 333 Disc & Shafts for Flue gases @ 2200°F</p>
<p>SASKPOWER Saskatoon, Sk. Canada. Coronach, SK. Canada</p>	<p>2-60" Double Block Slide Gate Valve, Flanged Ends, Carbon Steel Body and 316L Stainless Trim With Hydraulic Cylinder operator and Limit Switches For Double Block and Bleed confined space entry service 1 - 54" Same as above 1 - 48" Same as above 60" Blind Assemblies & Expansion Joints</p>
<p>TAMPA ELECTRIC COMPANY Polk County Gasifier Mulberry, Florida. USA</p>	<p>1-14" X 8" Refractory Lined Slide Gate ANSI 1500 2050°F Flue Gases @ 75PSIG, Supertherm Disc Ceramic Seats, Pneumatic operator</p>
<p>TRITON COAL/SHELL OIL Gasification Project Gillette, Wyoming. USA</p>	<p>1 – 48" Flex Wedge Slide Gate Valve, Flanged ends Emergency Vent Valve, With Bettis Linear Cylinder operator Valve Opens in 1 second in case of explosion in hot gas line To vent gases to stack. All 316L Body & Flanges with Hastelloy seat and disc, Double seat for zero leak service. Isolating process gases 1100°F @ 9Psig</p>