



## Frisch Engineered Products Inc. Partial Users List - Oil Refineries

<p><b>ADGAS</b> <b>Desalination Facility</b> Abu Dhabi, UAE</p>	<p>3-30" PS X 29" ID 150 ANSI Butterfly Valve, Reduced ID Carbon Steel Body lined with Ebonite, B148C95800 Aluminum Bronze Disc, Monel K500 Shafts. Manual gear operated 2-24" X 23" Same as Above 1-20" X 19" Same as Above 2-10" x 9" Same as Above</p>
<p><b>Desalination Facility</b></p>	<p>1-12" 150 ANSI Flanged Body Ebonite coated Cast Steel Body, Buna Seat Aluminum Bronze disc &amp; Monel K500 Shaft, Buna-N packing on bubble tight packing glands Teflon bearings, Aluminum Bronze Cover plate Face to Face = 102mm, Lever Operator included 4- 10" Same as above 6- 8" Same as above 7- 6" Same as above 6- 4" Same as above 7- 3" Same as above 2- 2" Same as above</p>
<p><b>Desalination Facility</b></p>	<p>1-60" ID Frisch Butterfly Valve 150 ANSI FF FL Body, Flanges to API 605 Marine epoxy coated Carbon Steel Body, Buna-N Seat and body liner Aluminum Bronze disc &amp; Monel K500 Shaft, Buna-N packing on bubble tight packing glands Teflon bearings 2- 18" Same as Above 2-16" Same as Above</p>
<p><b>Desalination Facility</b></p>	<p>1-20" X 19" ID 150 ANSI Butterfly Valve, Reduced ID Carbon Steel Body lined with Ebonite, B148C95800 Aluminum Bronze Disc, Monel K500 Shafts. Manual gear operated 7- 2" Same as above 8- 3" Same as above 12-4" Same as above 10- 6" Same as above 6- 8" Same as above</p>
<p><b>ALTONA (EXXON) PETROLEUM</b> <b>Australian Oil Refining</b> Melbourne, Australia</p>	<p>1 - 81" Cylinder Control BV For 1500°F Erosive Service 8" Refractory Lined, 316 SS Disc and Shaft with Stellite<sup>®</sup> 6B Hard Facing, RCC Gas service 1 - 66" Cylinder Control BV For 1500F Erosive Service 8" Refractory Lined, 316 SS Disc and Shaft with Stellite<sup>®</sup> 6B Hard Facing</p>



## Frisch Engineered Products Inc. Partial Users List - Oil Refineries

<b>ASHLAND (MARATHON) PETROLEUM RCC Complex</b> Ashland, Kentucky. USA	1 - 75" Butterfly Valve for RCC Gases @ 1500F and 3.8 PSIG TAG 2-116-HVC-10 1 - 89" Butterfly Valve for MRS Gases @ 1600F and 3.8 PSIG TAG 2-116-HVC-11
<b>BP/AMOCO</b> Whiting, Indiana. USA	2 - 16" X10"ID Refractory Lined Butterfly Valve with Haynes <sup>®</sup> Alloy HR160 <sup>®</sup> Internals for acid gas service 14Psig @ 1400°F 2 - 12" X 6"ID Refractory Lined Butterfly Valve
<b>CHEVRON ENERGY</b> El Segundo, California	1 - 36" Manual BV Heat Exchanger Outlet @ 550F
<b>GLOBAL OCTANES</b> Deer Park, Texas. USA	1 - 54"300 ANSI Butterfly Valve 347 Stainless Steel Construction For Flue Gas @ 1200F & 15 PSI Turbine Inlet Control Valve ANSI B16.104 CL IV Shut Off
<b>LG-CALTEX REFINING</b> Seoul, Korea	12", 16", 18" & 20" Butterfly Dampers All 304 Stainless With <i>Fisher</i> <sup>®</sup> 1052 Actuators with <i>Fisher</i> <sup>®</sup> DCV 6020 <i>Fieldvue</i> <sup>®</sup> Positioners.
<b>MARATHON OIL</b> Garyville, Louisiana, USA	1 - 42"CB100 BFV 2 - 96"GV105 Gate Valve Motorized 2 - 72" CB100 BFV
<b>MOBILE OIL</b> Chalmette, Louisiana, USA	20 - 4" Manual Slide Gate Valves For Soot Blower Isolation Service 5 PSI @ 1100F 5 - 4" Pneumatic Slide Gate Valves Soot Blower Isolation, 5 PSI @ 1100F



## Frisch Engineered Products Inc. Partial Users List - Oil Refineries

<p><b>MOTIVA ENTERPRISES</b> Port Arthur, Tx. USA</p>	<p>132" X 132" Refractory Lined Louver With 8 – Incoloy 800HT Parallel Blades With Remote Control Industries D/A Pneumatic Actuator Model RCI2886DA80, Complete with Fisher I/P Positioner. With Volume Tank and Accessories to fail louver open in</p>
<p><b>PETRONOR REFINERY</b> c/San Martin 5 Muskiz, Spain</p>	<p>1- 60" Rolling slide gate valve 150 ANSI B16.47 Series B Flanged Ends All 347H Stainless Steel, Incoloy 800H Shaft 1- 42" Same as above, 304 Stainless Steel 2- 60" Butterfly Valves 150 ANSI B16.47 Series B Flanged Ends All 347H Stainless Steel, Incoloy 800H Shaft 1- 42" Butterfly Valve Flanged Ends 304 Stainless Construction Waste Heat Boiler Isolation Valves</p>
<p><b>SHELL OIL</b> Norco, Louisiana, USA</p>	<p>1 - 20"RB102 BFV Refractory 347 SST internals Hot Gas Bypass on H<sub>2</sub>S Reaction Furnace For acid gases @ 1200F &amp; 15 Psig</p>
<p><b>SHELL REFINING</b> Geelong, Australia</p>	<p>1 - 54"300 ANSI Butterfly Valve All 304H with Rotork Hydraulic Actuator Turbo Expander Inlet Control 65 PSI @ 1400F on FCCU 1 - 32" 300 ANSI BFV All 304H with Hard Faced body &amp; disc with Rotork Hydraulic Actuator For Turbo Expander Bypass 65 PSI @ 1400F Flue gas w/catalyst Fines on FCCU</p>
<p><b>SHELL REFINING</b> <b>Sarnia Refinery</b> Sarnia, On. Canada</p>	<p>1 – 78" Inlet X 125" X 70" Outlet Slide Gate Valve Stack Breeching Isolation Valve. Flanged Ends A516GR70 Construction, 700F at 5 Psig</p>



## Frisch Engineered Products Inc. Partial Users List - Oil Refineries

---

<p><b>SHELL REFINING</b> <b>Montreal East Facility</b> Montreal, Que. Canada</p>	<p>2 – 64” Flanged Butterfly Valves All 304H Stainless Construction Machined Seat for Class III Shutoff 1500 F Service With Bettis Pneumatic actuator</p>
<p><b>SHELL INTERNATIONAL</b> <b>Na Kika Offshore Platform</b> Gulf of Mexico</p>	<p>5 – 48” 125 ANSI Flanged Butterfly Damper All 304 Stainless Construction, With metal Step Seat With Morin Spring Return Pneumatic Actuator and Fisher Fieldvue Smart Positioner 5 – 48” 125 ANSI Flanged Butterfly Damper All 304 Stainless Construction, With Tadpole Step Seat for FCI 70-2 Class III Shutoff With Morin Spring Return Pneumatic Actuator and Fisher Fieldvue Smart Positioner</p>
<p><b>TESORO GOLDEN EAGLE REFINERY,</b> Martinez , Ca. USA</p>	<p>75” x 67” Slide Gate Valve, Motor Operated A387 GR11 Construction, 304 Stainless Trim, Stellite Seat For Stack Isolation for waste Heat Boiler 1100F at 2 Psig</p>
<p><b>TESORO REFINERY</b> Mandan, ND. USA</p>	<p>1 – 8” x 4” Refractory Lined BFV Carbon Steel Body, 347H internals For 15 Psig @ 1400F.</p>